

Printer Model	Build Volume (XYZ)	Nozzle Size & Type	Printing Speed	Filament Compatibility	Nozzle Temperature Range	Bed Temperature Range	Connectivity & Control	Extruder
Cartesian Printers (Gantry Frame)								
Elegoo Neptune 4	225 x 225 x 265 mm	0.4 mm (Standard)	Up to 500 mm/s	PLA, PETG, TPU, ABS	Up to 300Â°C	Up to 110Â°C	USB, LAN (Wi-Fi with dongle)	Single Extruder
Elegoo Neptune 4 Pro	225 x 225 x 265 mm	0.4 mm (Standard)	Up to 500 mm/s	PLA, PETG, TPU, ABS	Up to 300Â°C	Up to 110Â°C	USB, LAN (Wi-Fi with dongle)	Single Extruder
Anycubic Kobra 3	250 x 250 x 260 mm	0.4 mm High Flow	Up to 600 mm/s	PLA, PETG, TPU, ABS, ASA	Up to 300Â°C	Up to 100Â°C	USB, Wi-Fi, Cloud	Single Extruder; compatible with ACE Pro for multi-color printing Single Extruder; includes ACE Pro for multi-color printing
Anycubic Kobra 3 Combo	250 x 250 x 260 mm	0.4 mm High Flow	Up to 600 mm/s	PLA, PETG, TPU, ABS, ASA	Up to 300Â°C	Up to 100Â°C	USB, Wi-Fi, Cloud	
Elegoo Neptune 4 Plus	320 x 320 x 400 mm	0.4 mm (Standard)	Up to 500 mm/s	PLA, PETG, TPU, ABS	Up to 300Â°C	Up to 110Â°C	USB, LAN (Wi-Fi with dongle)	Single Extruder
Elegoo Neptune 4 Max	420 x 420 x 480 mm	0.4 mm (Standard)	Up to 500 mm/s	PLA, PETG, TPU, ABS	Up to 300Â°C	Up to 110Â°C	USB, LAN (Wi-Fi with dongle)	Single Extruder

Cartesian Printers (Cube Frame)								
Elegoo OrangeStorm Giga	800 x 800 x 1000 mm	0.4 mm (Standard)	Up to 300 mm/s	PLA, PETG, TPU, Nylon	Up to 300Â°C	Up to 100Â°C	USB, LAN, Wi-Fi	Supports up to 4 simultaneous print heads; capable of mirror printing 4 models concurrently

CoreXY Printers (Enclosed Cube Frame)								
Anycubic Kobra S1	250 x 250 x 250 mm	0.4 mm (Standard); supports 0.2/0.6/0.8 mm	Up to 600 mm/s	PLA, PETG, TPU, ABS, ASA	Up to 300Â°C	Up to 120Â°C	USB, Wi-Fi	Single Extruder; compatible with ACE Pro for multi-color printing
Anycubic Kobra S1 Combo	250 x 250 x 250 mm	0.4 mm (Standard); supports 0.2/0.6/0.8 mm	Up to 600 mm/s	PLA, PETG, TPU, ABS, ASA	Up to 300Â°C	Up to 120Â°C	USB, Wi-Fi	Single Extruder; includes ACE Pro for multi-color printing
Elegoo Centauri Carbon	256 x 256 x 256 mm	0.4 mm Hardened Steel	Up to 500 mm/s	PLA, PETG, TPU, ABS, ASA, PLA-CF, PETG-CF, ABS-CF, ASA-CF, PET-CF, PA CF, PET, PC, PA	Up to 320Â°C	Up to 110Â°C	LAN, Wi-Fi, USB	Single Extruder
Creality K2 Plus	350 x 350 x 350 mm	0.4 mm (Standard)	Up to 600 mm/s	PLA, ABS, PETG, PA-CF, PLA-CF, PET, ASA, PPA-CF	Up to 300Â°C	Up to 120Â°C	USB Drive, Ethernet, Wi-Fi	Single Extruder
Creality K2 Plus Combo	350 x 350 x 350 mm	0.4 mm (Standard)	Up to 600 mm/s	PLA, ABS, PETG, PA-CF, PLA-CF, PET, ASA, PPA-CF	Up to 300Â°C	Up to 120Â°C	USB Drive, Ethernet, Wi-Fi	Single Extruder

CoreXY Printers (Open Cube Frame)								
Elegoo Centauri	256 x 256 x 256 mm	0.4 mm Hardened Steel	Up to 500 mm/s	PLA, PETG, TPU, ABS, ASA	Up to 320A°C	Up to 110Â°C	LAN, Wi-Fi, USB	Single Extruder

